


VIEW	TOLERANCE	
	0-10	±1
	11-250	±5
	261-500	±10
UNIT: mm	501-1000	±20
	1001-3000	±50
	3001-5000	±100
	5001->	±150






△ Order Code : 1110D-XX-H

Housing  
Number of contact : 4 to 40 pin

**TTAF  
APPROVAL**

△ Material : Nylon 66 UL 94V-0

Voltage Rating : 250V AC,DC  
Current Rating : 3A AC,DC  
Withstanding Voltage : 1000V/minute  
Insulation Resistance : 1000M Ω Min  
Temperature Range : -25°C ~ + 85°C



Contact No.	Dimensions(mm)		
	A	B	C
2x2	2.00	5.90	4.60
2x3	4.00	7.90	6.60
2x4	6.00	9.90	8.60
2x5	8.00	11.90	10.60
2x6	10.00	13.90	12.60
2x7	12.00	15.90	14.60
2x8	14.00	17.90	16.60
2x9	16.00	19.90	18.60
2x10	18.00	21.90	20.60
2x11	20.00	23.90	22.60
2x12	22.00	25.90	24.60
2x13	24.00	27.90	26.60
2x14	26.00	29.90	28.60
2x15	28.00	31.90	30.60
2x16	30.00	33.90	32.60
2x17	32.00	35.90	34.60
2x18	34.00	37.90	36.60
2x19	36.00	39.90	38.60
2x20	38.00	41.90	40.60

Date	08.04.2014	Rev.	Revision Detail	Rev.Dt.	Rev.by	Part No		
Designed by	Yeşim AKSOY	-				<b>1110D-XX-H</b>		
Checked by	Fatih BOLACA							
						Drawing Nr.	Scale	Sheet No
						-	NONE	1/1