



VIEW	TOLERANCE	
	0-10	±1
	11-250	±5
UNIT: mm	261-500	±10
	501-1000	±20
	1001-3000	±50
	3001-5000	±100
	5001->	±150



Order Code : 1302-XX-S




Straight

Number of contact : 10 to 64 pin A


**TTAF
APPROVAL**

Material : Nylon 66 UL 94V-0
Pin Material : Brass

Voltage Rating : 500V AC,DC
Current Rating : 1AMP
Withstanding Voltage : 500V/minute
Insulation Resistance : 1000M Ω Min
Temperature Range : -55°C ~ + 105°C



P.C.B. LAYOUT



Contact No.	Dimensions(mm)		
	A	B	C
10	20.30	18.10	10.16
12	22.84	20.64	12.70
14	25.38	23.18	15.24
16	27.92	25.72	17.78
20	33.00	30.80	22.86
26	40.62	38.42	30.48
30	45.70	43.50	35.56
34	50.78	48.58	40.64
40	58.40	56.20	48.26
50	71.10	68.90	60.96
60	83.80	81.60	73.66
64	88.88	86.68	78.74

Date	03.11.2014	Rev.	-	Revision Detail	Rev.Dt.	Rev.by	Part No		
Designed by	Yeşim AKSOY						1302-XX-S		
Checked by	Fatih BOLACA								
							Drawing Nr.	Scale	Sheet No
							-	NONE	1/1